




SOILTEK S60B ROTARY MACHINE GENERAL SPECIFICATION



Whilst every care has been taken to ensure the correctness of the information contained within this document, no liability can be accepted for any errors or omissions. Published by Roger Bullivant Limited



Rig Designation		Soiltek S60B		
Weight & Dimensions				
Gross Weight	15.75t	16.80t	17.80t	
Operating Length		5.34m		
Operating Height	3.96m	6.83m	10.82m	
Overall Width (500mm Tracks)	2.20m	2.20m expanding to 2.70m		
Transport Length	5.02m	6.86m	10.85m	
Transport Height		3.26m		
Mast Articulation - Fore & Aft	±5°	±5°	±2°	
Mast Articulation - Side to Side	±5°	±5°	±2°	
Foot Travel		450mm		
Piling System				

Drill Head	RT4600			
Rotary Head Torque	1.50Tm @ 79rpm / 3.00Tm @ 40rpm / 4.30Tm @ 19rpm			
Available Auger Range	Ø300mm to Ø600mm (750mm in short mast mode)			
Head Travel	1.40m	4.25m	8.20m	

Ground Pressure

FPS Rig Loading Data Sheet available



Whilst every care has been taken to ensure the correctness of the information contained within this document, no liability can be accepted for any errors or omissions. Published by Roger Bullivant Limited